Skin protection cream LINDESA®

LINDESA®

Design

- Slightly greasy skin protection and care cream that contains natural beeswax and is absorbed quickly
- Strengthens the skin's defences
- Prevents damage to the skin caused by external sources
- Also contains chamomile
- Silicone-free and no greasy residue

Applications

To nourish slightly irritated skin.





68001 Skin protection cream pr88[®]/Skin protection fluid pr88[®] liquid

Pr) URSULA RATH

- Non-greasy, water-soluble, silicone-free skin protection cream with a barrier function between the skin and substance
- Leaves no greasy residue
- The skin's functions, such as releasing moisture and sense of touch, are not affected

Applications


For stubborn dirt caused by oil, paint, tar and bitumen products, synthetic resin, silicone and adhesives.

68001 101-102

Skin protection cream in a tin.

68001 103

Skin protection fluid in a spray bottle.







68001 101

pr 88





68001 102

68006 202

68006 201

68003 102

68006

Skin protection cream/lotion GREVEN®

GREVEN

68006 101-102 **GREVEN® REMO TEC**

Design

- Water-soluble and residue-free skin protection
- A protective film prevents dirt from building up and makes cleaning your skin easier
- Grease-free and silicone-free.

Applications

For stubborn, oily or dry dirt such as waste oils, varnish, paint, tar and bitumen.

68006 201-202 **GREVEN® MULTI TEC**

Design

- Skin protection lotion with a barrier function against water-soluble and water-insoluble substances
- D-Panthenol and vitamin E also have an anti-inflammatory effect and support the skin's natural regeneration
- Silicone-free.

Applications

For undefined skin irritations or changing working substances, also for wearing gloves.

Product	Content ml	Design	68006
REMO TEC	100	Tube	101
REMO TEC	2000	Collapsible bottle	102
MULTI TEC	100	Bottle	201
MULTI TEC	2000	Collapsible bottle	202

2000 mle . 68006 102 GREVEN 2000 mle GREVEN

68006 101

68002 - 68003

Skin protection ointment/cream

SCJohnson

68002

Skin protection ointment Travabon® classic Design

Water-soluble, grease-free and silicone-free, with high solids content, dirt-binding, scented. Dirt-binding emulsifier makes cleaning your skin easier. Improved protection thanks to protective skin pigments. The ability to grip is not lost.

To protect against oily, water-insoluble substances such as oil, paint, graphite, metallic dust, soot.

68003

Skin protection cream Stokoderm® aqua pure Design

Soft cream with repair effect to protect skin when working in damp and wet conditions. Light moisturising properties and is absorbed quickly. Strengthens, stabilises and regenerates the skin barrier.

Applications

When coming into contact with water-based substances such as coolants and aqueous solutions, when wearing gloves and closed protective clothing.

Travabon® classic Stokoderm® aqua pure Content Design ml 100 101 101 Tube 1000 Soft bottle 102

68002 102 68003 101

68002 101



68.1

REINOL

Design

- Very effective hand cleaner with softwood flour as a natural abrasive
- Moisturising to provide optimum skin compatibility, even with repeated daily use

Design

Bucket

Design

Bucket

Tin

Tin

Applications

Light to medium soiling such as oil, grease, coolants, rubber abrasion or soot.

68000

Dispenser

68011

101

102

101

102

68000 102





10 I 68010 - 68011

Content

500 ml

Hand cleaner and dispenser

W

68010

Hand cleaner

Design

HHW hand cleaner now boasts natural corn cob meal to clean deep into the pores. It also moisturises your skin. With skin-friendly and pH-neutral blend of surfactants, dermatologically tested. Silicone-free.

Applications

Heavy soiling in industrial applications, such as oil, grease, dust, lubricants and paint.

101

68011 101

Dispenser

Includes wall bracket for three-litre tin.

Cleaner

68010

Dispenser For ten-litre buckets.

68010 102 + 68011 102



68010 101	+ 68011	101





10 68024

3

Skin cleansing lotion GREVEN®

GREVEN

68024 101-102 GREVEN® SOFT B/RS

Contents

Design

Special tools / PPE

- Skin cleansing lotion with no abrasives, but excellent cleaning performance and tailored to skin's pH-value
- Moisturises, free of soaps and solvents.

Applications

For moderate to heavy soiling caused by substances such as grease, oil, metal dust or soot.

68024 201-202 **GREVEN® ACTIVE PEARLS**

Design

- Hand cleaner with dirt-binding, soft castor wax pearls ASP (Active Soft Pearls)
- No sharp or hard abrasives, resulting in less damage to skin than when using conventional, coarse hand cleaners
- Free of soaps and solvents.

Applications

For heavy soiling caused by grease, oil, metallic dust, graphite or soot. Recommended when washing hands frequently.

Product	Content ml	Design	68024
SOFT B/RS	250	Tube	101
SOFT B/RS	2000	Collapsible bottle	102
ACTIVE PEARLS	250	Tube	201
ACTIVE PEARLS	2000	Collapsible bottle	202



68024 201

68024 101

68024 102

68005

Hand cleaner

SCJohnson

PROFESSIONAL A family company"

Note:

STOKO® collapsible dispenser for 1000-ml bottles or 2000-ml soft bottles, see art. no. 68030.

68005 101

Hand cleaner Kresto® Classic

Design

Contains special solvents. Paste with abrasive ASTOPON® (refined, ground walnut shells), with skin protection agent EUCORNOL®. Excellent at cleaning.

Applications

For extremely stubborn dirt such as oil, grease, lubricants.

68005 100+103

Hand cleaner Solopol® strong

Design

Paste with abrasive ASTOPON® (refined, ground walnut shells) and skin protection agent EUCOR-NOL® as well as aloe vera. Especially gentle on the skin, excellent at cleaning.

Applications

For solvent-free hand cleaning with a high abrasive content, for extreme soiling such as oil, grease, soot, graphite, lubricants.

68005 099+102

Hand cleaner Solopol® natural Design

Paste with abrasive ASTOPON® (refined, ground walnut shells) and skin protection agent EUCOR-NOL® as well as aloe vera. Leaves skin feeling noticeably nourished.

Applications


For very heavy soiling such as oil, grease, soot, metallic dust, lubricants

68005 099

68005 102

68005 103





Skin care cream

GREVEN

68028 101-102 Special cream C

- Cream is absorbed quickly to nourish and regenerate damaged skin
- Moisturising, silicone-free

Applications

For very damaged skin. Suitable for all skin types.

68028 202-301 **GREVEN® UREA** Design

- Lightly moisturising skin care cream, which absorbs extremely well, for the hands and face
- Excellent regeneration effect on very damaged
- With urea and beeswax
- Silicone-free, unscented

Applications

For very damaged, dry and sensitive skin.

Product	Contents ml	Design	68028	
Special cream C	100	Tube		101
Special cream C	2000	Collapsible bottle		102
GREVEN® UREA	2000	Collapsible bottle		202
GREVEN® UREA	100	Tube		301 👤



68026 - 68027

Skin care

SCJohnson PROFESSIONAL A family company"

68026

Skin care cream Stokolan® Classic Design

- Skin care cream that absorbs quickly, with soothing and regenerative effect for the hands and
- Extremely gentle on the skin and provides outstanding skin care
- Silicone-free

Applications

For very damaged skin, suitable for all skin types.

Note:

STOKO® collapsible dispenser for 1000-ml bottles or 2000-ml soft bottles, see art. no. 68030.

68027

Skin care gel Stokolan® Light Gel Design

- Intensive, moisturising and very fast-acting moisturising gel for hands and face
- Contains creatine the skin's very own energy source - and glycerine and urea
- Silicone-free

Applications

For normal skin.









68026 101

68026 102

68030

STOKO® dispenser

SCJohnson

PROFESSIONAL A family company"

STOKO Vario® mat

Design

- Stainless steel housing
- Coated in white

Applications

Wall dispenser for adjustable dispensing of 1000-ml and 2000-ml soft bottles for STOKO® products.

H x W x D	68030	
mm		
322 x 126 x 140		101



68030

Disposable nitrile gloves Dermatril®



Design

- Disposable nitrile glove, powder-free
- Fingertips lightly roughened to give a better grip
- Excellent resistance to tearing
- Non sterile, can be worn on either hand

Applications:

- Laboratories and research fields
- Chemical industry
- Food and electrical industries
- Cleaning and maintenance work
- Product protection

68075 100-101

Dermatril® 740

- With rolled edge
- EN 420, EN 374:2016 KPT, EN 455, AQL 0.65, Cat. III

68075 200-201 Dermatril® P 743

- With a long cuff
- EN 420, EN 374:2016 JKLOPT, EN 455, AQL 0.65, Cat. III



					Dermatril® 740	Dern	natril® P 743	
Size	Overall length	Layer thickness	Design	Pack =	68075		68075	
	approx. mm	mm		pieces				
9	250	0.11	In dispenser box	100		100		200
10	280	0.20	In dispenser box	50		101		201

10	280	0.20	In a
68080	Disposable la	tex aloves	;

Design

- Seamless
- Powdered
- Can be worn on either hand

Size	Design	Pack = pieces	68080	
10	In dispenser box	100		101



68085 Cotton jersey gloves

Design

- Cotton jersey glove with gusset for increased flexibility and comfort
- White-bleached
- EN 420, Cat. I

Applications:

- Installation, maintenance and packaging tasks
- Product protection
- Can be worn as a liner glove

Size	Pack = Pair	68085	
M (7 - 8)	12		101
L (10)	12		102
XL (13)	12		103



68086 Assembly gloves

uvex[®]

rubipor XS

Design

- Extremely lightweight, breathable assembly glove
- High level of dexterity and sense of touch thanks to new shape
- Fingertips, thumb and palm with NBR waterproofing
- Lining: cotton/interlock
- Coating: NBR special (nitrile rubber)
- EN 388:2016 Level 1110X

Applications:

- Precision/small parts assembly
- Sorting/quality control tasks
- Product protection

Size	Length approx. cm	Colour	Pack = Pair	68086
9	27	White	1	101



68089

Protective gloves

uvex[®]

rubiflex NB27

Design

- High-quality protective glove with excellent sense of touch
- Extremely durable, seamless coating
- Lining: cotton/interlock
- Coating: Special NBR (nitrile rubber)
- EN 388:2016 Level 3111X

Applications:

- Metalworking
- Maintenance
- Painting, maintenance and inspection tasks
- Good resistance to oil, grease and fuels







10

Size	Length	Pack =	68090	
	cm	Pair		



40

Design

- Long style with fabric on back of the hand and fabric cuff with wrist guard and elasticated band

68100 101

- Synthetic leather, lined palm, white drill
- Colour: yellow

68100 102

- Pig grain leather, lined palm
- CE cat. I

68100 103

- Upholstery leather, excellent quality, reinforced palm, canvas cuffs, bright colours

68100 104

- -Stierkopf natural-
- Leather, excellent quality, rubberised cuffs, lined palm, minimum thickness of 1.2 mm
- EN 388:2016 Level 2133X, Cat. II

Size	Pack = Pair	68100	
10	12		101
10	12		102
10	12		103
10	1		104







68100 103



Special tools / PPE

68100 102







68101

Cotton gloves Sahara® 100



Design

- High-quality cotton jersey glove with yellow special nitrile coating, open back of the hand and knitted cuff
- Excellent mechanical strength and breathability combined with a very good fit
- Moisture-repellent
 - Free of plasticisers
 - EN 420, EN 388:2016 Level 3111X, Cat. II

Applications:

- Automotive and metalworking industries
- Assembly and production
- Construction industry
- Working with oily and wet parts

Size	Pack = Pair	68101	
7	10		101
8	10		102
9	10		103
10	10		104



68108

Nylon gloves Gripmaster®

Design

- Nylon glove with micro-porous latex coating on the palm
- Excellent tactile feel and provides very secure grip on oilyand slippery parts
- EN 420, EN 388:2003 Level 2122, Cat. II

Applications:

- Working with oily and slippery workpieces
- Assembly and maintenance
- Precision engineering
- Automotive industry

Size	Pack = Pair	68108	
8	12		101
9	12		102
10	12		103



Nylon gloves Camapur® Comfort 626



Design

- Nylon knitted glove with polyurethane coating on the palm and on the back of the hand over the knuckles
- High degree of mechanical resilience
- Excellent fit
- Extremely good sensitivity and breathability
- Provides an excellent grip
- EN 420, EN 388:2016 Level 2121X, Cat. II

Applications:

- The electrical industry
- Precision engineering
- Automotive industry
- Assembly and maintenance
- Working with greasy and oily workpieces

Size	Pack = Pair	68103	
7	10		101
8	10		102
9	10		103
10	10		104



68109

Nylon fine knit gloves ActiveGrip™ Advance



Design

- Nylon fine-knit glove with black Micro-Finish® nitrile coating on the palm
- Anatomical fit
- Excellent resistance to wear, non-slip, breathable
- EN 420, EN 388:2016 Level 4121X, Cat. II

Applications:

- Assembly and maintenance tasks in dry, damp or oily conditions
- Automotive industry
- Construction industry and mechanical engineering



Size	Pack = Pair	68109	
9 (L)	12		101
10 (XL)	12		102
11 (XXL)	12		103

68110

Nitrile gloves

Design

- Cotton jersey glove with blue nitrile coating and open back of the hand for good breathability
- High degree of abrasion resistance with good fit
- EN420, EN388, Cat. II

Applications:

- Automotive and metalworking industries
- Assembly and production
- Transport and sorting tasks
- Construction industry

68100 100

Design - With cuff

68100 101 Design

- With knitted cuff

68110 103

uvex.

profi ergo ENB 20A

PROFI-CLASSIC protective gloves

Knitted cuff, DIN EN 388:2016 Level 2121X, excellent grip in dry/wet conditions, very comfortable.







Size	Pack = Pair	68110	
10	12		100
10	12		101
9	1		103

68115

Protective heat gloves

Design

- Knitted cotton glove with double-sided, heat-resistant nitrile coating
- Contact heat protection up to 250°C
- EN 420, EN 388:2016 Level 1232X, EN 407 02XXXX, Cat. II

Applications:

- Light to moderate thermal conditions









Cut protection gloves Camapur® Cut 620



Design

- HPPE high-performance fibre knitted glove with grey polyurethane coating on the palm
- Excellent fit and good sensitivity coupled with high level of cut protection properties
- Washable
- EN 420, EN 388:2016 Level 4X42B, Cat. I

Applications:

- Sheet metalworking and metalworking with moderate cutting hazards
- Automotive industry
- Assembly and maintenance



Size	Pack = Pair	68117	
8	1		101
9	1		102
10	1		103

68118

Dyneema® knitted gloves

Design

- Dyneema® fibre knitted glove with a polyurethane coating on the palm to give an excellent grip and added mechanical resilience
- Good sensitivity and tactile feel
- Washable
- EN 420, EN 388:2016 Level 4343C, Cat. II

Applications:

- Sheet metalworking and metal processing
- Working with sharp-edged, dry or oily workpieces
- Maintenance tasks that come with risk of being cut



Size	Pack = Pair	68118	
8	1		101
10	1		102

68120

Cut protection gloves

Design

- Kevlar® medium-knit glove with double-sided PVC nubs for improved grip
- Longer knitted cuff to protect the wrist
- EN 420, EN 388:2003 Level 1340, Cat. II

Applications:

- Working with sharp-edged and/or slippery workpieces
- Packaging and transportation



Size	Pack = Pair	68120	
10	1		102

Info

HHW occupational safety catalogues

More gloves as well as general information regarding hand and skin protection can be found in our latest

PPE catalogue Skin protection/Gloves/Cleaning

Request your copy at info@hhw.de.







Hearing protection

68150

Ear plugs

Honeywell

HOWARD LEIGHT

68150 101

Foam ear plugs Laserlight

Design

- With a smooth outer skin
- Tapered and moulded
- Adapt perfectly to the contours of the ear canal and are easy to insert and seal
- Sold in pairs in bags

68150 201

Banded ear plugs QB1


Design

- Light and comfortable
- The special, ergonomic shape ensures the ear plugs are at the required distance, such as when placed on the work surface.

68150 202

Replacement ear plugs

For banded ear plugs, art. no. 68150 201.





68150 201

68150 101



Pack =	SNR value dB	68150	
200 pairs	35		101
1 pcs	26		201
50 pairs	-		202

68160

Hearing protection box

Design

Special tools / PPE

- Made from ABS plastic, blue
- Dust- and splash-proof
- Easy to mount by screwing or gluing in place
- Incl. fastening materials



Dimension	68160	
cm		
23.6 x 22.5 x 12.5		104

68161 - 68162

Ear defenders

Honeywell

Leightning L2F High Visibility Design

- Foldable headband allows for practical storage
- Luminous green defenders ensure excellent visibility in bad weather or in the dark
- Reflective headband is highly visible when light shines on it, offering greater safety - Air Flow Control technology provides optimum
- insulation capacity at all frequencies
- Tested in accordance with EN 352-1

Applications

Ideal for wearing at night, in low lighting conditions and poor weather conditions.

68162 101

Leightning L2 Design

- Spring steel headband for working in extreme
- The soft foam padding of the headband and the comfortable ear pads (replaceable) offer maximum comfort, even when worn for long periods of time
- A perfect fit on all head sizes is guaranteed thanks to the telescopic height adjustment
- Tested in accordance with EN 352-1

Applications

For moderate noise ranges and long periods of use.





Туре	SNR value	Weight	68161 .	68162	
	dB	g			
Leightning L2F	32	236	10	11	
Leightning L2	31	222			101

3M PELTOR

68163 101 Optime I

Design

- Very versatile and particularly lightweight (180 g)
- These ear defenders have a slim profile, but feature a generous depth inside
- Easy to combine with other equipment
- The ideal choice for those needing all-round ear defenders for short or longer periods of use
- Tested in accordance with EN 352-1/352-3

Applications

For low-level noise exposure. In workshops, plumbing tasks, in print shops, for hobbies and leisure use.

68163 201 Optime II Design

- The Optime II has been developed for high-level noise exposure and provides effective protection, even at very low frequencies
- The sealing rings are filled with a mixture of liquid and foam and ensure an optimal seal when light pressure is applied
- Excellent comfort is maintained, even during longer periods of use
- The headbands are flexible and can be adjusted as required
- Tested in accordance with EN 352-1/352-3

Applications

For high-level noise exposure. When working with constructionequipment, pneumatic drills and in agricultural applications.

68163 301 Optime III Design

- The Optime III is the best choice to protect against extreme noise exposure
- Double protectors keep resonance in the defender to a minimum. In doing so, maximum insulation at high frequencies is achieved yet signals and speech are still easy to perceive.
- The acoustic connection between the interior and the space between the protectors ensure optimum insulation at low frequencies
- Wide, softly padded band
- Tested in accordance with EN 352-1/352-3

Applications

For extreme noise exposure. For use in airports, mines and machine rooms.

68163 101







			_	_
Туре	SNR value	Weight	68163	
	dB	g		
Optime I	27	180		
Optime II	31	210		
Optime III	35	285		

Info

HHW occupational safety catalogues

More products and general information regarding head protection/breathing protection/eye protection and fall arresters can be found in our latest

PPE catalogue Head protection/Fall arresters

Request your copy at info@hhw.de.

() = Items with prices in brackets partly available from stock







Info

Respiratory protection - Protection levels according to EN 149:2001

Protection level	VGW*	Remark/Restriction
FFP1	4	Against non-toxic dusts and aerosols based on water and oil. Not against carcinogenic and radioactive substances and airborne biological agents of risk groups 2 and 3 and enzymes
FFP2	10	Against harmful and carcinogenic dusts, smoke and aerosols based on water and oil. Not against radioactive substances and airborne biological agents of risk group 3 and enzymes
FFP3	30	Against harmful and carcinogenic dusts, smoke and aerosols based on water and oil. Against radioactive substances and airborne biological agents of risk group 3 and enzymes

^{*} Multiple of the limit value

68200

Breathing masks



68200 201

Design

- Reinforced outer shell
- Soft inner shell
- Malleable nose clip
- FFP1 D protection level, EN 149:2001

Applications

Protects against solid, non-toxic particles.

68200 202

Design

- Solid outer casing, malleable nose clip, exhalation valve
- Low resistance, very comfortable
- Foam inner seal
- Tacked head strap
- FFP2 D protection level, EN 149:2001

Applications

Protects against solid, harmful, less toxic substan-



68200 201

Protection level	Pack = Units	68200	
FFP1 D	20		201
FFP2 D	10		202

68202

Breathing masks

Honeywell

68202 101

Design

- FFP1 in accordance with EN 149:2001
- Breathing mask with soft and gentle sealing lip for optimal tightness around the nose
- A tear-resistant and elasticated strap makes for a tiaht fit
- The mask is free of PVC, silicone and latex
- Colour of the nose clip: yellow

Applications

Solid and liquid aerosols (dust, aerosols) up to four times the limit value.

68202 102

Design

- FFP2 in accordance with EN 149:2001
- Breathing mask with soft and gentle sealing lip for optimal tightness around the nose
- A tear-resistant and elasticated strap makes for a
- The mask is free of PVC, silicone and latex
- Colour of the nose clip: green

Applications

Solid and liquid aerosols (dust, aerosols) up to 10 times the limit value.

68202 103

Design

- FFP2 in accordance with EN 149:2001
- Breathing mask with soft and gentle sealing lip for optimal tightness around the nose
- With exhalation valve for even more comfort
- A tear-resistant and elasticated strap makes for a tight fit
- The mask is free of PVC, silicone and latex
- Colour of the nose clip: green

Applications

Solid and liquid aerosols (dust, aerosols) up to 10 times the limit value.

68202 104

Design

- FFP3 D in accordance with EN 149:2001
- Folding mask in hygienic packs of one with both a supple, soft sealing lip around the nose and an exhalation valve
- The mask offers minimal breathing resistance, even when the filter material has to work hard to filter particles
- The mask is free of PVC, silicone and latex
- Colour of the nose clip: red

Applications

Solid and liquid aerosols (dust, aerosols) up to 30 times the limit value.

Protection level	Pack = Units	68202	
FFP1	20		101
FFP2	20		102
FFP2	20		103
FFP3 D	10		104



68202 102



68202 103



68202 104







Design

- Moulded mask body
- The nose body is individually adaptable

68203 201

Breathing mask FFP2

Applications

Ten times the limit value for fine dust.

68203 202-203

Design

- Breathing masks with patented Cool Flow exhalation valve for maximum breathing comfort
- Glasses will not mist up

68203 202

Breathing mask FFP2

Design

- With Cool Flow exhalation valve

Applications

Ten times the limit value for fine dust.

68203 203

Breathing mask FFP2 D

Design

- With Cool Flow exhalation valve, adjustable straps and sealing lip

Applications

Ten times the limit value for fine dust.





68203 202

68206 101

Special tools / PPE





68206

FFP2

FFP2

FFP2 D

Protection level

Breathing masks from the Aura™ 9300+Gen3 Series

3M

Design

The revamped breathing mask 3MTM AuraTM 9300+Gen3 is now in its third generation.

The new 3MTM Cool FlowTM comfort valve offers excellent dissipation of exhaled heat and moisture and significantly reduces exhalation resistance further.

Pack =

Units

20

10

New positioning aids allow wearers to open the mask hygienically, then mould it and put it on. The new high-performance filter technology offers significantly improved respiratory comfort, coupled with reduced volume and weight. A durable and comfortable fabric strap guarantees the best fit. The three-piece design with integrated nose clip adapts to any face shape. Hygienic packs of one.

68206 101

Type 9312+Gen3

Design

- FP1 NR D mV in accordance with EN 149:2001 + A1:2009

68206 201

Type 9322+Gen3

Design

- FFP2 NR D mV in accordance with EN 149:2001 + A1:2009

68206 301

Type 9332+Gen3

Design

- FFP3 NR D mV in accordance with EN 149:2001 + A1:2009



Protection level	Pack = Units	68206	
FFP1	10		101
FFP2	10		201
FFP3	10		301

68215 Breathing mask 4279 (maintenance-free)

3M

Design

- Maintenance-free mask for maximum safety and ease of use
- Two large active carbon filter elements ensure minimal breathing resistance
- Large field of vision thanks to low-profile design
- Parabolic exhalation valve reduces build up of heat
- Soft and gentle mask material
- Lightweight and well-balanced design
- Elasticated strap with head holder
- Easy-to-fasten neck straps

- Protection level of FFABEK1P3D in accordance with EN 405:2002

Applications

Organic vapours, inorganic and acidic gases, as well as ammonia up to ten times the MAK value or 1000 ml/m3, whichever value comes first.

Fine dusts up to 30 times the limit value.

When working with ammonia, methylamine, chlorine, bleach, hydrochloric acid, sulphur dioxide, hydrogen sulphide, solvents.

68215	
	101





Safety goggles MAX T7

W

Design

- Lightweight, dual-lens safety goggles with flexible, non-slip sports temples for a comfortable fit
- Soft nose pads ensure a perfect fit
- The nose pads can be removed for cleaning
- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

For working indoors and outdoors.





Lens	Frame	68240
Clear	Crystal/black	201
Tinted grey	Crystal/black	202

68242

Safety goggles MAX W3

##W

Design

Special tools / PPE

- Indoor/outdoor safety goggles with slightly silver, reflective polycarbonate lens for use in varying lighting conditions
- The soft nose bridge and flexible, length-adjustable temples offer a secure fit
- The large visor protects the eyebrow area and offers good, all-round vision
- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

For working in varying lighting conditions indoors and outdoors.



Lens	Frame	68242
Reflective silver	Black/orange	101

68246

Safety goggles MAX C4



Design

- Polycarbonate
- Very light
- Optimum fit and coverage
- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

In workshops, assembly areas and laboratories as well as for use as visitor goggles.





Lens	Frame	68246
Clear	Clear	101
Grey	Grey	102

68248 Safety goggles MA	X Z8
-------------------------	------

Design

- Sturdy metal temples

- Soft, PVC-coated temple ends for comfortable
- Large visor protects the eyebrow area and offers good, all-round vision
- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

In workshops, assembly facilities, extreme operating conditions.



Lens	Frame	68248
Clear	Metal/silver	101

Safety goggles MAX A1

H:W

Design

- The classic among safety goggles with elasticated nylon temples
- Two components form the flexible temple ends with very soft nubs, which ensure improved positioning of these goggles
- Temple length and tilt can be adjusted to fit the individual wearer
- Side guard offers optimum safety

- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

In workshops and laboratories. Protects during drilling, milling and grinding tasks.



	1
68249	
	101





68243

Safety goggles MAX XR

Frame

Blue/red

Blue/red



Lens

Clear

Tinted grey

Design

- Non-slip soft pads on the temple ends The ends can be tilted
- Unlimited all-round vision

- Lens with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

In workshops, assembly facilities and laboratories.





68244

Safety goggles MAX SL

H:W

Design

 Casual dual-lens safety goggles with length-adjustable nylon temples and a soft, comfortable nose pad ensure a perfect fit

- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166-168

Applications

In workshops and laboratories and for assembly tasks.

Lens	Frame	68244
Clear	Grey	101



68245

Safety goggles MAX K9



Design

- Mist-free polycarbonate lens
- Nylon temples, adjustable in length and can be tilted at the joint
- Soft PVC nose pads
- Lenses with 100% UV protection, scratch-resistant and mist-free
 - Tested in accordance with EN 166-168

Applications

For working outdoors.

Lens	Frame	68245
Clear	Grey	101



68250

Safety goggles MAX V1

##W

Design

- With durable polycarbonate side guard
- Extremely shock-resistant and scratch-resistant
- Can be worn over standard prescription glasses
- Tested in accordance with EN 166-168

Applications

Protects when sawing, planing, drilling, milling, grinding, polishing and for lab work.

Lens	Frame	68250	
Clear	Transparent	201	





68.13

Design

- Goggles with clear polycarbonate temples and
- Ideal for wearing over prescription glasses
- Tested in accordance with EN 166



Lens	Frame	68250
Clear	Clear	301

68257

Safety goggles Terminator Plus



Design

- Modern safety goggles with a sporty design
- An additional rubber lip on the top edge of the frame stops foreign objects getting inside the
- The temple lengths and tilt adjustment allow wears to adjust the goggles to suit them, thus ensuring a perfect fit
- Soft temples that do not pinch
- Polycarbonate lens, clear, 100% UV protection, scratch-resistant
- Tested in accordance with EN 166-168, EN 170

Applications

For grinding, turning and milling tasks, precision engineering tasks, assembly tasks and lab work.



Lens	Frame	68257	
Clear	Black/mint		101

68257

Safety goggles Terminator small



Special tools / PPE

- Specifically for smaller head shapes, goggles have an all-round, tight seal
- Soft temples
- Optimum wearer acceptance and a perfect fit thanks to the adjustable tilt and temple length
- Polycarbonate lens, clear, 100% UV protection, scratch-resistant
- Tested in accordance with EN 166-168, EN 170



For precision engineering tasks, assembly tasks and lab work, goggles for visitors.



Lens	Frame	68257
Clear	White	201

68252

Safety goggles Millennia

Honeywell

Design

- Extremely comfortable safety goggles that are light to wear and offer a perfect fit
- Undistorted view
- Supplied with adjustable, flexible goggle strap
- Lens with 100% UV protection, scratch-resistant

Tested in accordance with EN 166-168, EN 170

Applications

When wearers' heads are in extreme positions: in workshops and in assembly facilities.



Lens	Frame	68252	
Clear	Blue		101

68253

Safety goggles XC®

Honeywell

Design

- Safety goggles with an integrated ventilation duct in the forehead strap
- The forehead strap is covered with a flexible, shockresistant and non-slip elastomer to offer, together with the lens geometry, optimum protection
- The temple length and the tilt of the lens can be adjusted individually
- Lens with HydroShield lasting anti-fog coating
- Clear lens, UV 400, scratch-resistant and mist-free
- Tested in accordance with EN 166-168, EN 170

Applications

For grinding, milling and turning tasks, precision engineering tasks, in workshops and for assembly tasks and lab work.

Lens	Frame	68253
Clear	Blue	101



www.hhw.de Fax order hotline: 0800 0 915910

68257 101

68257 201

68252

68280

Safety goggles pheos 9192

uvex

Design

- Safety goggles with modern, fashionable look
- Perfect, all-round protection
- Large field of vision thanks to duospheric lens
- Excellent ventilation thanks to integrated uvex climazone frame concept
- Goggles stay in place by means of hard/soft technology with non-slip components on the temple ends
- Lenses with 100% UV protection, scratch-resistant and mist-free
- Tested in accordance with EN 166, EN 170



Lens	Frame	68280
Clear	Light grey	101

68281

Safety goggles futura 9180

uvex^{*}

Design

- Lightweight safety goggles with virtually unlimited field of vision
- Maximum comfort and tight feel thanks to excellent
- Temples can be tilted as much/little as required
- Temple length can be adjusted to suit the wearer
- Tested in accordance with EN 166-168, EN 170



Lens	Frame	Goggles 68281		68281	
Clear	Brown/transparent		101		102

68283

Safety goggles i-vo

uvex

Design

- Soft components in sensitive areas, as well as comfortable padding in the temples offer long-lasting comfort
- Lens with 100% UV protection, scratch-resistant and mist-free HC-AF
- Tested in accordance with EN 166-168, EN 170

Applications

For grinding, turning and milling tasks, precision engineering tasks, assembly tasks and lab work.



		Goggles	Spare lens	
Lens	Frame	68283 .	68283	
Clear	Blue/orange	10	1	201

68284

Safety goggles skyper 9195

uvex

Design

- Super-lightweight safety goggles with unrestricted lateral perception
- Lens and temples made of high-impact-resistant plastic
- Highly flexible, comfortable temples mean the goggles fit without pinching
- Temple length individually adaptable with integrated stop lock
- The temples can be inclined to give a perfect goggle fit
- The frosted side guard provides added protection against glare
- 100% UV protection
- Tested in accordance with EN 166-168, EN 170



		Goggles	Spare lens	
Lens	Frame	68284	68284	
Clear	Black	1	01	102
Clear	Black	1	01	

68271

Goggles for wearing over glasses

uvex

type 9161

Design

- Fit over all prescription glasses
- Unlimited peripheral perception through the superpanoramic lens with a 180° field of vision
- Excellent, pressure-free fit
- Effective indirect ventilation thanks to special temple design with optimal lateral guard
- The temple ends can be adjusted to four lengths, maximum comfort
- Tested in accordance with EN 166-168, EN 170

Applications

To provide protection during sawing, planing, drilling, milling, sanding and polishing tasks and lab work.







68.15

W

Design

- Chemical safety goggles with indirect ventilation via four button-shaped valves
- Mist-free polycarbonate lens
- Tested in accordance with EN 166

Applications

To provide protection in laboratories and when working with chemicals.



68268

Frame 68268 Lens Clear Clear 101

68264

Panorama full-vision safety goggles ultravision 9301

uvex

Design

- Unrestricted peripheral view thanks to super-panoramic lens (colourless)
- With 180° field of vision
- Completely tight yet pressure-free fit
- Optimal fit and improved comfort thanks to the soft face pad and special nosepad

Spare lens 68264

102

Ventilation system, mist-free anti-fog lens

101

- Ideal for people who wear glasses

Tested in accordance with EN 166-168, EN 170

68264 102 Spare lens, clear

- Polycarbonate
- High degree of mechanical resilience



-	~	•	_
Ы	82	2h	h

Full-vision safety goggles ultrasonic 9302

Goggles

uvex[®]

Lens

Clear

Design

Special tools / PPE

- Extraordinarily comfortable: Thanks to the combination of two different materials (hard components/soft components), wearing the goggles for long periods does not lead to any pressure problems
- The flexible, soft components nestle against the wearer's individual face shape and guarantee allround side protection of the eye area, even for glasses wearers
- The excellent ventilation ensures a pleasant feeling and no eye irritation
- Wide panoramic field of vision, plus faster and easier lens changes thanks to the innovative clip technology
- Tested in accordance with EN 166-168, EN 170





· ·		Goggles		Spare lens	
Lens	Frame	68265		68265	
Clear	Orange/grey		101		103
Clear	Grey/black		102		103

68289 Goggle cleaning wipes

Frame

Grey/transparent

uvex^{*}

Design

- Cleaning wipes, silicone-free
- Individually wrapped

Applications

Suitable for all lenses.





68289

68290 203

68290

Boxes for safety goggles

TORM

Design

- Made from ABS plastic, blue
- Dust- and splash-proof
- The box for safety goggles features two mounting holes and is designed to be permanently installed anywhere where users' eyes are at risk from sparks, chips, light flashes etc.
- Incl. fastening materials

Dimensions	For safety	68290
cm	goggles Quantity	
23.6 x 12.0 x	12.0 1	201
23.6 x 22.5 x	12.5 4	202
23.6 x 31.5 x	20.0 12	203

Applications

Ideal for the clean and compact storage of safety goggles. Placed within easy reach at workstations, entrances to production areas, in laboratories, to be used by visitors.





68290 202



Bump protection hats First Base 3 Classic and Elite

SCOTT

Design

- The newly developed, flexible inner shell with micro-perforated sides and indirect ventilation in the crown area guarantees optimum air circulation
- The moulded shell design adapts perfectly to different head sizes and shapes, and boasts a secure and comfortable fit
- The machine-washable microfibre fabric with large ventilation mesh on the sides and the absorbent sweatband significantly reduce dampness and heat inside the bump protection hat
- Worn over the ears to further improve the individual fit and compatibility with other items of PPE
- Tested in accordance with EN 812 A1

68330 201-204

First Base 3 Classic

Design

- The third generation of the SCOTT bump protection hat

68330 301-302 First Base 3 Elite

Design

- The new First Base 3 Elite in bi-colour design for a modern appearance
- With additional ventilation mesh in the crown area
- Reflective piping goes around the hat to provide visibility in the dark and in low lighting conditions





	Classic	Elite
Colour	68330	68330
Black	201	
Navy blue	202	
Royal blue	203	
Grey	204	
Black/grey		301
Navy blue/grey		302



68134

Back belt MAX



Size

S

Design

- Hazard sources for spinal injury include monotonous assembly-line work, long periods of standing and lifting heavy loads
- In combination with the correct lifting technique, the belt helps to keep the risk of back injuries to a minimum

Length cm

> 69-81 79-91

89-104

68134	
	101
	102


- The conical shape adapts perfectly to the wearer's body and is comfortable to wear
- The special hip and rib contour provides added comfort
- Furthermore, the tailored shape ensures a perfect fit
- The **one-way hook and loop system** and slid'n grip fastener not only guarantee added safety, but also **excellent ease of use**

Size	Length cm	68134	
XL	101-114		104
XXL	112-124		105





Info



Information on the use of personal protective equipment to prevent falls, to restrain users and to save lives.

The applicable rules and regulations of the employer's liability insurance coverage in compliance with regulations BGR 198 and BGR 199, as well as the accident prevention regulations, must be observed.

Fall arrester equipment must be in place (excerpt):

- At workplaces or traffic routes, at and over water or other liquid or solid substances in which it is possible to sink; this applies regardless of the height from which you can fall
- At a fall height of more than 1.0 m on stairways without railings and stairway landings, wall openings, machine control stations, in addition to openings (skylights, ventilation shafts etc.) not equipped with a load-bearing cover securely held in place
- At a fall height of more than 2.0 m at all other workplaces and traffic routes.

Notwithstanding this, the following applies:

- At workplaces and traffic routes on roofs from a fall height of 3.0 m and above
- \bullet On walls and tasks carried out on windows from a fall height of 5.0 m and above.

The fall arrest system

The fall arrest system is made up of various individual components, which can be combined depending on the area of application and requirement.

The attachment point

- In accordance with EN 795
- For example, tripod, webbing sling, minifix, permanent systems.

The lanyard

- In accordance with EN 353-2, EN 354/355, EN 360 or EN 358
- For example, guided type fall arresters, Shockyards, fall dampeners, retractable type fall arresters.

The harness

- In accordance with EN 364, EN 358 or EN 813
- For example, safety harness and rescue harnesses, tether, seat harness.



Standards

Depending on the area of application and the purpose, items of personal fall protective equipment are subject to various standards:



EN 358 Retaining straps

For holding in the working position and for restraint in areas where there is a risk of falling (such as when working on flat roofs). The retaining lugs are usually located on the side around the pelvic bone.



EN 361

For use in climbing protection in conjunction with guided type fall arresters including a rigid anchor line. Climbing protection (such as when working on towers, masts). The climbing protection eyelets are usually located on the abdominal belt, in the centre in front of the body.



EN 361 Full body harness

For securing workers in areas with a risk of falling and for arresting falls (such as when working on towers, masts, building overhangs). The arrester eyelets are located on the back between the shoulder blades (dorsal) or on the chest area (sternal).



Rescue eyelet

Other components/selection:

EN 341 Descender devices

EN 353-1 Guided type fall arresters including a rigid anchor line
EN 353-2 Guided type fall arresters including a flexible anchor line

EN 354 Lanyards

EN 355 Energy absorbers

EN 360 Retractable type fall arresters

EN 363 Fall arrest systems
EN 795 Attachment point



Applications:



Industrial use

Travel/overhead line construction





Telecommunications



Maintenance



Steel construction

Fire departments

Construction



Events



Fall arrest system

SKYLOTEC

Set comprises:

Safety harness EN 361, type CS 2 with front and rear arrester eyelet. Sling EN 354 and EN 795, type LOOP 22 kN, 2 m in length. Guided type fall arrester in accordance with EN 353-2, type SKN 10 m in length. Core sheath rope with carabiner FS 51, in a transport case.

Note:

For technical data relating to safety harnesses and fall arresters, refer to art. no. 68350 ff.

68340	
	301





68350

Safety harnesses



68350 401-402

ARG 30

Design

Powerful all-round safety harness for industrial and trade use. Individually adjustable slotted buckles on the shoulders and legs make the harness faster to put on and take off. The central steel chest eyelet is permitted as a safety harness in accordance with EN 361.

68350 401



68350 402 ARG 30 HRS

Design

Lateral attachment points in accordance with EN 358, climbing protection eyelet in accordance with EN 361 in combination with EN 352-1, back support.

68350 402



68350 403

ARG 31 Skyfizz Lifter Click Design

The individually adjustable harness is ideal for working without positioning ropes or other aids. Extremely heavy-duty steel front and rear arrester eyelet in accordance with **EN 361**. The comfortable back pad distributes the load evenly. The click fasteners allow ease of use and make the harness easier to put on.

68350 403



Туре	Weight	68350	
	approx. kg		
ARG 30	1.1		4
ARG 30 HRS	1.6		4
ARG 31	1.6		4

68357

Lanyards

SKYLOTEC

68357 101-102 BFD SK 12

Design

- Lanyard with fall dampener
- Durable and abrasion-resistant core sheath rope with one FS-51 and one FS-90 steel carabiner
- Tested in accordance with EN 354, EN 355

68357 103 BFD Y SK 12

Design

- Dual-strand lanyard with fall dampener
- Durable and abrasion-resistant core sheath rope with one FS-51 and two FS-90 steel carabiners
- Tested in accordance with EN 354, EN 355



Туре	Length m	68357	
BFD SK 12	1.5		101
BFD SK 12	2.0		102
BFD Y SK 12	1.5		103



68351 - 68353

Guided type fall arresters EN 353-2



68351

Pole restraint rope

Design

Ergogrip SK 12 in compliance with **EN 358**, Ovaloy Tri and FS 51 carabiners. Rope diameter 12 mm. For use in the side retaining lugs in accordance with EN 358. The Ergogrip runner is very small, lightweight and ergonomic. It can be continuously adjusted on the rope.

Note:

Work positioning ropes are used only for the positioning of the workstation.

68352

Design

Guided type steel fall arrester, on flexible anchor line. Incl. automatic snap hook, type FS 51. Energy absorption takes place by gliding on a sheathed-core rope 11 mm in diameter. As soon as the fall arrester stops, it restrains the secured worker at height in an extremely short reaction time, with no unpleasant ripping noise. This reduces the shock of the fall significantly in the first moment. The worker feels safe. The impact is reduced.

68353 Ergogrip SK 16 Design

The Ergogrip is a length-adjustable fall arrester and is used for secure and flexible work positioning. It can be used as a guided type fall arrester or as a work positioning rope. The special, core-sheathed 16-mm rope can withstand edge loads and also heavy loads.

EN 353-2, EN 358.





	Adjustable		Guided type		Adjustable	
Fall arrester	68351		68352		68353	
Rope length m						
2		101				
5				301		301
10				302		302
15				303		303
20				304		

68355

Slings



Design

- Can withstand edge loads

- Strength: 35 kN

- EN 354, EN 795



68355

Length	68355	
m		
1		101
2		102

H: M

Info

Excerpt from accident prevention regulations:

The new German technical occupational health and safety regulations ASR A4.3 "First aid rooms, resources and facilities" for first aid provide standardised and legally binding guidelines for all workplaces, whether in heavy industry, workshops, small businesses, the public sector or in educational institutions:

- In administrative companies and commerce:
- Up to 50 employees, 1 x DIN 13157 small,
- > 50 employees, 1 x DIN 13169 large,
- > 300 employees, 1 x DIN 13169 per 300 employees.
- In manufacturing and processing plants:

Up to 20 employees, 1 x DIN 13157 small,

- > 20 employees, 1 x DIN 13169 large,
- > 100 employees, 1 x DIN 13169 per 100 employees.

- On construction sites:

Up to 10 employees, 1 x DIN 13157 small,

- > 10 employees, 1 x DIN 13169 large,
- > 50 employees, 1 x DIN 13169 per 50 employees.

One large first aid kit DIN 13169 can also be replaced with two small first aid kits DIN 13157.

68400

Large first aid kits in accordance with DIN 13169

STHNGEN®

68400 201

First aid kit MT-CD

Design

ABS plastic, orange in colour, wall bracket with 90° stop lock, sturdy handle and rotary catches, two halves of the case equal in size, perimeter rubber seal, transparent cover plates, adjustable internal dividers, sealing device, security seal.

Includes contents in accordance with DIN 13169.

68400 202

First aid cabinet Rome

Design

Sheet steel, white in colour, two doors, lockable, two adjustable shelves, two drawers, doors each have three storage trays, folding storage panel.

Includes contents in accordance with DIN 13169.

68400 203

First aid box Oslo

Design

Sheet steel, painted white, frame and lid from a single piece, rounded edges, profile seal, two case handles, two latches.

Includes contents in accordance with DIN 13169.

68400 211

Contents

Design

All contents in accordance with DIN 13169 for refilling and filling existing first aid kits.





68400 202







68400 211

DIN 13169

Туре	Size	68400
	mm	
First aid box	400 x 300 x 150	201
First aid cabinet	404 x 462 x 170	202
First aid kit	350 x 250 x 100	203
Contents	-	211



68401

Small first aid kits in accordance with DIN 13157

5DHNGEN®

68401 201

First aid kit Quick-CD

Design

ABS plastic, orange in colour, wall bracket with 90° stop lock, sturdy handle and rotary catches, two halves of the case equal in size, perimeter rubber seal, transparent cover plates, adjustable internal dividers, sealing device, security seal.

Includes contents in accordance with DIN 13157.

68401 202

First aid cabinet Heidelberg

Design

Sheet steel, painted white, single door, lockable, one adjustable shelf, folding storage panel, door with

Includes contents in accordance with DIN 13157.

68401 203

First aid kit Kiel

Design

Made of high-impact-resistant plastic, white, with hinge and locking tabs.

Includes contents in accordance with DIN 13157.

68401 211 Contents

Design

All contents in accordance with DIN 13157 for refilling and filling existing first aid kits.





68401 202

68401 201

68401 203









		DIN 10107
Туре	Size	68401
	mm	
First aid box	260 x 170 x 110	201
First aid cabinet	302 x 362 x 140	202
First aid kit	260 x 160 x 80	203
Contents	-	211

Vehicle first aid kit DIN 13164





5DHNGEN®

68402

Design

- Made of highly impact-resistant plastic
- With hinge and locking tabs
- Colour: black
- Includes contents in accordance with DIN 13164

	DIN 10104	
Size	68402	
mm		
260 x 160 x 80		101





68403

First-aid case SPEZIAL

STHNGEN®

Design

- Includes basic equipment DIN 13157 plus extensions
- Colour: orange
- Size: 400 x 300 x 150 mm
- Additional content includes more plasters, universal dressings, oculavNIT® eye rinse, hand and wound cleaning cloths, splinter tweezers, packs of pressure bandages, aluderm®-aluplast plaster dressings

In maintenance and repair businesses, technical workshops.

Note:

First aid kits for other occupations available on request.



DIN 13157 plus extensions

First aid kit for occupational group	68403	
Workshop		102

68406

QuickFix plaster dispenser

plum

-Design

Special tools / PPE

The lockable QuickFix dispenser is just 23 cm wide and 13.5 cm high and, despite its compact size, can accommodate 90 plasters. The plasters are immediately to hand and are automatically released when pulled out. The system can therefore be operated with one hand, without getting other plasters dirty. QuickFix - quick, easy and hygienic first aid for minor injuries.

68406 101

Plaster dispenser Water Resistant

Design

Waterproof, ideal for wet working environments. Filled with 2 x 45 plasters.

68406 102

Refill kit Water Resistant

Design

6 packs of 45 plasters.

68406 201

Plaster dispenser Elastic

Design

Particularly breathable and elastic fabric plasters that follow the movement of the skin. Filled with 2 x 45 plasters.

68406 202

Refill kit Elastic

6 packs of 45 plasters.

68406 301

Plaster dispenser Detectable

Design

Elastic and visually striking blue plasters with integrated metal surface for detection by metal detectors. Suitable for use in the food industry. Filled with 2 x 45 plasters.

68406 302

Refill kit Detectable

Design

6 packs of 45 plasters.

68406 101



68406 102



Туре	Plaster dispenser 68406	Refill kit 68406	
Water Resistant		101	102
Elastic		201	202
Detectable		301	302

68402



STHNGEN®

Design

ABS plastic practical dispenser with wall bracket and mounting kit, orange in colour. Three compartments, transparent, hinged lid with tunnel compartment.

Contains:

30 aluderm®-aluplast strips 7.2 x 1.9 cm,

30 aluderm®-aluplast strips 7.2 x 2.5 cm,

25 aluderm®-aluplast fingertip plasters,

20 aluderm®-aluplast finger bandages 12 x 2 cm,

10 aluderm®-aluplast knuckle dressings,

1 emergency treatment document block with

40 sheets.

All plasters are hygienically sealed in individual packs.

Note:

aluderm®-aluplast plasters do not stick to the wound, do not fray, are breathable, highly absorbent, promote healing and formation of new skin, are hypoallergenic, physiologically safe, free of optical brighteners and chemical binders.





Dispenser H x W x D mm	68407	
160 x 122 x 57		101

68408

Accessories -First Aid-

STHNGEN®

68408 101

Set of additional plasters

Design

A total of 116 aluderm®-aluplast plaster dressings with aluminised wound dressing pads, each plaster is individually wrapped including finger dressings, fingertips and knuckle plasters, plaster strips, colourful children's plasters, silk adhesive plaster strips. In plastic box 161 x 118 x 50 mm, with hinged transparent lid, blue in colour.

Applications

Additional contents for first aid cabinet or stand-alone first aid kit in the workplace/office.

() = Items with prices in brackets partly available from stock

68408 102-103

oculavNIT®eye rinse

Ready-to-use sterile solution for instant rinsing of eyes and conjunctival sac, in particular following burns caused by acids, alkalis, pepper spray, CS tear gas.

250 ml per bottle, maintenance-free, shelf life of three years. Safety lock.

68408 102

oculavNIT® box

Design

Contents: 4 oculavNIT® eye rinse bottles, instant set for eye injuries.

In plastic box, 260 x 160 x 80 mm, with practical wall bracket, orange in colour.

68408 103

Single bottle containing 250 ml of sterile solution.







68408 103

Special tools / PPE

Туре	Contents Quantity	Contents ml	68408
Set of additional plasters	116	-	101
Eye rinse, box	-	4 x 250	102
Eye rinse, single	-	250	103



Secutex Pro 5/6

Design

Anti-static chemical protective overall that is dustproof with limited resistance to spray. Hood with elasticated band, dual zip, zip trim, elasticated back, arms and legs. The overall protects against splashes of aggressive, liquid chemicals and is permeable to air and water vapour. The combined polypropylene spunbonded fabric backing and polyatylene-laminate combine maximum protection and abrasion resistance.

Protection class: Cat. III, Type 5, 6. Virus protection-certified to EN 14126.

Areas of application include production and bottling in the food, pharmaceutical and cosmetics industries, production in the chemical industry, veterinary protection.

68501

Tritex Pro blue

Design

Special tools / PPE

Dustproof with limited resistance to spray. Anti-static finish. Breathable three-ply SMS material. Even when worn for long periods, the robust suit prevents the build up of heat and moisture. Hood with elasticated band, dual zip, zip trim, elasticated waist, arms and legs. Protection class: Cat. III, Type 5, 6.

Applications

For asbestos disposal, processing of material containing glass fibre, for maintenance and renovati-

68502

Painttex-Plus

Protects against harmful fine dust. Durable, antistatic, wearproof and lint-free. Breathable three-ply SMS material. Hood with elasticated band, dual zip, zip trim, elasticated waist, arms and legs.

Protection class: Cat. III, Type 5.

Applications

For industrial and automotive painters, for renovation work, clean-up work and asbestos removal.

68503

Tritex Pro white

Design

Dustproof overalls made from three-ply SMS fabric, breathable, anti-static. Lightweight. Hood with elasticated band, dual zip, zip trim, elasticated waist, arms and legs.

Protection class: Cat. III, Type 5, 6.

Applications

For asbestos removal, processing of material containing glass fibre, for maintenance and renovation work, for use in the food industry.









Size	68500		68501		68502		68503	
XL		101		101		101		101
XXL		102		102		102		102

68555

PVC hi-vis vests

Design

- Made of PVC-coated, knitted fabric
- Manufactured in accordance with EN 471 Class 2
- With a double ring fastener and reflective stripes
- Packaged in a PE bag

Size	Colour	68555	
One size fits all	Orange/red, fluorescent		101
One size fits all	Yellow fluorescent		201

68555 201

68555 101

68563

Trucker waistcoat

Design

High collar, kidney protection, various external pockets, one internal pocket, concealed zip, red/black-check cotton lining.

Upper material: 65% polyester, 35% cotton.

Filling: 100% polyester. Lining: 100% cotton flannel.

Size	Colour	68563	
M	Black		101
L	Black		102
XL	Black		103
XXL	Black		104
XXXL	Black		105



Info

Safety shoes in accordance with EN ISO 20345

The European Standards (EN) for shoes used in industrial and commercial fields.

EN ISO 20345 - Test energy of toe cap 200 joules, EN ISO 20346 - Test energy of toe cap 100 joules,

EN ISO 20347 - no toe cap

EN ISO 20345 Areas of application

SB Meets all basic requirements of EN ISO 20345. Open heel, protective toe caps with 200 joules of resistance. **S1**

Full or split leather. In addition to the basic requirements: closed heel, energy absorption capacity, anti-static, protective toe cap

with a resistance of 200 joules. Application: In industry, crafts and trade, dry areas.

S1P Same as S1, but with the addition of a puncture-resistant midsole running through the shoe.

Same as S1, suitable for working on wet floors, therefore impermeable to water, able to absorb water vapour. Application: In dry S2

areas, indoors and outdoors.

Meets all the requirements of S2, with the addition of a puncture-resistant midsole running through the shoe. S3

Application: In dry/wet areas, indoors/outdoors, for use as construction shoes/boots and when there is the risk of nail punctures.

68713

Low-cut safety shoe Kayak Black S1P ESD





Design

- Shaft: extremely breathable textile and microfibre
- Lining: breathable and wearproof textile lining,
- high degree of moisture absorption and release
- Footbed: EVANIT ESD, thermoformed, perforated footbed with breathable coating
- Outsole: EVA/TPU, with low electrical resistance
- Midsole: APT plate, metal-free

 Protective 	e cap: Aluminium
- Width: 11	Mondopoint

- Plus: TPU front cap, anti-torsion support, ESD-tested, DGUV 112-191

- EN ISO 20345 S1P SRC



German Size	68713
36	101
37	102
38	103
39	104

German Size	68/13	
40		105
41		106
42		107
43		108

German Size	68713
44	109
45	110
46	111
47	112

68714

Low-cut safety shoe Potency S1P ESD BOA

COFRA®

Design

- Shaft: extremely breathable textile and leather
- Lining: SANY-DRY® breathable and wearproof textile lining, excellent moisture absorption and release
- Footbed: COFRA SOFT ESD, anatomically shaped, soft polyurethane with shock-absorbing effect and high degree of slip resistance
- Outsole: PU/TPU, with low electrical resistance

-	Mi	ds	ole:	ΑF	T	р	late,	m	etal	l-free
	_									

- Protective cap: Aluminium - Width: 11 Mondopoint

- Plus: BOA® lacing system, ESD-tested

- EN ISO 20345 S1P SRC





German	68714	
Size		
36		101
37		102
38		103
30		10/

German Size	68714
40	105
41	106
42	107
43	108

German Size	68714	
44		109
45		110
46		111

68715

Low-cut safety shoe Cruiser Black S3

COFRA

42

Design

- Shaft: water-repellent nubuck leather, breathable material inserts
- Lining: SANY-DRY® breathable and wearproof textile lining, excellent moisture absorption and distribution
- Footbed: COFRA SOFT ESD, anatomically shaped, soft polyurethane with shock-absorbing effect and high degree of slip resistance

-	Ou	tso	le:	Ы	U/	TP	U
---	----	-----	-----	---	----	----	---

- Midsole: APT plate, metal-free

- Protective cap: Plastic

- Width: 11 Mondopoint

- Plus: Leather front cap, anti-torsion support, 100% metal-free

- EN ISO 20345 S3 SRC



German Size	68715	
43	104	
44	105	
45	106	



German	68715	
Size		
46		107
47		108

68.25

Low-cut safety shoe Zatopek S3



Design

- Shaft: water-repellent leather
- Lining: SANY-DRY® breathable, wearproof, high degree of moisture absorption and release
- Footbed: COFRA-Soft anatomically shaped, soft polyurethane with shock-absorbing effect and high degree of slip resistance

- Outsole: PU/TPU

- Midsole: APT plate, metal-free - Protective cap: Aluminium - Width: 11 Mondopoint

- Plus: Extremely lightweight and flat outsole

- EN ISO 20345 S3 SRC



German Size	68727
36	101
37	102
38	103
39	104

German Size	68727
40	105
41	106
42	107
43	108

German Size	68727	
44		109
45		110
46		111
47		112

Info

HHW occupational safety catalogues

Many other safety shoes as well as accessories

can be found in our latest

occupational safety catalogue Safety shoes/Accessories

Request your copy at info@hhw.de.















